




O環尺寸表 (依內徑排序)

O-Ring Size List (Inner Diameter List)



材質	JIS 記號	1 種 A	1 種 B	3 種	4 種 C	4 種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09016-3	16	22	3	
*	09016-3.5	16	23	3.5	
*	09016-4	16	24	4	
*	09016-4.5	16	25	4.5	
*	09016-5	16	26	5	
*	09016.2-1.5	16.2	19.2	1.5	
*	09016.3-2.4	16.3	21.1	2.4	
	08908	16.36	20.78	2.21	AS-908
*	02017	16.4	22.6	3.1	G-17
*	09016.5-1	16.5	18.5	1	Ss-165
*	09016.5-1.5	16.5	19.5	1.5	
*	09016.5-2	16.5	20.5	2	
*	09016.5-2.5	16.5	21.5	2.5	
*	09016.5-2.7	16.5	21.9	2.7	
*	09016.56-1.78	16.56	20.12	1.78	
*	09016.8-1.2	16.8	19.2	1.2	
	071017	16.8	20.6	1.9	JASO-1017
*	09016.8-2	16.8	20.8	2	
*	01017	16.8	21.6	2.4	P-17
	08313	16.81	27.47	5.33	AS-313
*	09016.9-2.7	16.9	22.3	2.7	
*	09017-1	17	19	1	Ss-170
*	09017-1.5	17	20	1.5	
*	09017-2	17	21	2	
*	09017-2.5	17	22	2.5	
*	09017-3	17	23	3	
*	09017-4	17	25	4	
*	09017-4.5	17	26	4.5	
*	09017-5	17	27	5	
*	09017-6	17	29	6	
	08209	17.04	24.1	3.53	AS-209
*	09017.1-1.6	17.1	20.3	1.6	
	08115	17.12	22.36	2.62	AS-115
	08017	17.17	20.73	1.78	AS-017
*	09017.3-2.4	17.3	22.1	2.4	
*	02018	17.4	23.6	3.1	G-18
*	09017.5-1	17.5	19.5	1	Ss-175
	04018	17.5	20.5	1.5	S-18
*	09017.5-2	17.5	21.5	2	
*	09017.5-2.5	17.5	22.5	2.5	

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09017.5-3	17.5	23.5	3	
*	09017.5-3.5	17.5	24.5	3.5	
*	09017.5-4	17.5	25.5	4	V-18
*	09017.6-2.7	17.6	23	2.7	
*	09017.7-3	17.7	23.7	3	
	071018	17.8	21.6	1.9	JASO-1018
*	09017.8-2	17.8	21.8	2	
	01018	17.8	22.6	2.4	P-18
*	09017.86-2.62	17.86	23.1	2.62	
	08909	17.94	22.86	2.46	AS-909
*	09018-0.7	18	19.4	0.7	
*	09018-1	18	20	1	Ss-180
*	09018-1.5	18	21	1.5	
*	09018-1.7	18	21.4	1.7	
*	09018-2	18	22	2	
*	09018-2.2	18	22.4	2.2	
*	09018-2.5	18	23	2.5	
*	09018-2.8	18	23.6	2.8	
*	09018-3	18	24	3	
*	09018-3.5	18	25	3.5	
*	09018-4	18	26	4	
*	09018-4.5	18	27	4.5	
*	09018-5	18	28	5	
*	09018-6	18	30	6	
*	09018-7	18	32	7	
*	09018.1-1.6	18.1	21.3	1.6	
*	09018.2-2.5	18.2	23.2	2.5	
*	09018.2-3	18.2	24.2	3	
*	09018.2-4.6	18.2	27.4	4.6	
*	09018.3-1.5	18.3	21.3	1.5	
*	09018.3-2.4	18.3	23.1	2.4	
*	09018.3-3.65	18.3	25.6	3.65	
*	09018.4-2.7	18.4	23.8	2.7	
*	02019	18.4	24.6	3.1	G-19
*	09018.42-1.02	18.42	20.46	1.02	
	08314	18.42	29.08	5.33	AS-314
*	09018.5-1	18.5	20.5	1	Ss-185
*	09018.5-1.5	18.5	21.5	1.5	
*	09018.5-2	18.5	22.5	2	
*	09018.5-2.5	18.5	23.5	2.5	

* 符號代表國際規範外，CNL 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)



材質	JIS 記號	1 種 A	1 種 B	3 種	4 種 C	4 種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09018.5-3	18.5	24.5	3	
*	09018.5-5	18.5	28.5	5	
	08210	18.64	25.7	3.53	AS-210
*	09018.67-0.71	18.67	20.09	0.71	
	08116	18.72	23.96	2.62	AS-116
	08018	18.77	22.33	1.78	AS-018
	071019	18.8	22.6	1.9	JASO-1019
*	01019	18.8	23.6	2.4	P-19
*	09018.9-2.8	18.9	24.5	2.8	
*	09019-0.7	19	20.4	0.7	
*	09019-1	19	21	1	Ss-190
*	09019-1.5	19	22	1.5	
*	09019-2	19	23	2	
*	09019-2.5	19	24	2.5	
*	09019-3	19	25	3	
*	09019-3.5	19	26	3.5	
*	09019-4	19	27	4	
*	09019-5	19	29	5	
*	09019-6	19	31	6	
*	09019.1-1.6	19.1	22.3	1.6	
	08910	19.18	24.1	2.46	AS-910
*	09019.2-1.65	19.2	22.5	1.65	
*	09019.2-2.5	19.2	24.2	2.5	
*	09019.2-3	19.2	25.2	3	
*	09019.3-2.4	19.3	24.1	2.4	
*	09019.3-2.5	19.3	24.3	2.5	
*	09019.4-2.1	19.4	23.6	2.1	
*	02020	19.4	25.6	3.1	G-20
*	09019.5-1	19.5	21.5	1	Ss-195
	04020	19.5	22.5	1.5	S-20
*	09019.5-2.5	19.5	24.5	2.5	
*	09019.5-3	19.5	25.5	3	
*	09019.5-3.5	19.5	26.5	3.5	
*	09019.5-4	19.5	27.5	4	V-20
	071020	19.8	23.6	1.9	JASO-1020
	01020	19.8	24.6	2.4	P-20
*	09019.8-3.5	19.8	26.8	3.5	
*	09019.81-1.98	19.81	23.77	1.98	
	08315	19.99	30.65	5.33	AS-315
*	09020-1	20	22	1	Ss-200

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09020-1.2	20	22.4	1.2	
*	09020-1.3	20	22.6	1.3	
*	09020-1.5	20	23	1.5	
*	09020-2	20	24	2	
*	09020-2.5	20	25	2.5	
*	09020-2.6	20	25.2	2.6	
*	09020-3	20	26	3	
*	09020-3.5	20	27	3.5	
*	09020-4	20	28	4	
*	09020-4.5	20	29	4.5	
*	09020-5	20	30	5	Gm-020
*	09020-6	20	32	6	
*	09020-8	20	36	8	
*	09020-10	20	40	10	
*	09020-12	20	44	12	
*	09020.1-1.6	20.1	23.3	1.6	
	08211	20.22	27.28	3.53	AS-211
	08117	20.29	25.53	2.62	AS-117
*	09020.3-2.4	20.3	25.1	2.4	
	08019	20.35	23.91	1.78	AS-019
*	02021	20.4	26.6	3.1	G-21
*	09020.5-0.7	20.5	21.9	0.7	
*	09020.5-1	20.5	22.5	1	
*	09020.5-1.5	20.5	23.5	1.5	
*	09020.5-2	20.5	24.5	2	
*	09020.5-2.5	20.5	25.5	2.5	
*	09020.5-3	20.5	26.5	3	
*	09020.5-3.5	20.5	27.5	3.5	
*	09020.5-4	20.5	28.5	4	V-21
*	09020.7-3	20.7	26.7	3	
	01021	20.8	25.6	2.4	P-21
*	09020.8-3	20.8	26.8	3	
*	09021-1	21	23	1	
*	09021-1.5	21	24	1.5	
*	09021-1.8	21	24.6	1.8	
	071021	21	24.8	1.9	JASO-1021
*	09021-2	21	25	2	
*	09021-2.5	21	26	2.5	
*	09021-3	21	27	3	
*	09021-3.5	21	28	3.5	


O 環 尺 寸

* 符號代表國際規範外， 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)



O環尺寸表 (依內徑排序)

O-Ring Size List (Inner Diameter List)



材質	JIS 記號	1種 A	1種 B	3種	4種 C	4種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09021-4	21	29	4	
*	09021-4.5	21	30	4.5	
*	09021-5	21	31	5	
*	09021-6	21	33	6	
*	09021.3-2.4	21.3	26.1	2.4	
*	09021.3-3	21.3	27.3	3	
*	09021.3-3.6	21.3	28.5	3.6	
*	09021.4-1	21.4	23.4	1	
*	02022	21.4	27.6	3.1	G-22
*	09021.4-3.5	21.4	28.4	3.5	
	04022	21.5	24.5	1.5	S-22
*	09021.5-2	21.5	25.5	2	
*	09021.5-2.4	21.5	26.3	2.4	
*	09021.5-2.5	21.5	26.5	2.5	
*	09021.5-4	21.5	29.5	4	V-22
	08316	21.59	32.25	5.33	AS-316
*	09021.6-1.5	21.6	24.6	1.5	
*	09021.7-3	21.7	27.7	3	
	01022A	21.7	28.7	3.5	P-22A
	01022	21.8	26.6	2.4	P-22
*	09021.8-3.2	21.8	28.2	3.2	
	08212	21.82	28.88	3.53	AS-212
	04022.4	21.9	25.9	2	S-22.4
	08118	21.9	27.14	2.62	AS-118
	08911	21.92	27.82	2.95	AS-911
	08020	21.95	25.51	1.78	AS-020
*	09022-0.9	22	23.8	0.9	
*	09022-1	22	24	1	
*	09022-1.5	22	25	1.5	
*	09022-2	22	26	2	
*	09022-2.5	22	27	2.5	
*	09022-3	22	28	3	
*	09022-4	22	30	4	
*	09022-4.5	22	31	4.5	
*	09022-5	22	32	5	
*	09022-6	22	34	6	
*	09022.1-1.6	22.1	25.3	1.6	
	071022	22.1	25.9	1.9	JASO-1022
	072022	22.1	26.9	2.4	JASO-2022
	01022.4	22.1	29.1	3.5	P-22.4

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09022.3-3	22.3	28.3	3	
*	02023	22.4	28.6	3.1	G-23
*	09022.5-1.5	22.5	25.5	1.5	
*	09022.5-2	22.5	26.5	2	
*	09022.5-2.5	22.5	27.5	2.5	
*	09022.5-3	22.5	28.5	3	
*	09022.7-0.8	22.7	24.3	0.8	
*	09022.7-3.5	22.7	29.7	3.5	
*	09023-0.6	23	24.2	0.6	
*	09023-1	23	25	1	
*	09023-1.5	23	26	1.5	
*	09023-2	23	27	2	
*	09023-2.5	23	28	2.5	
*	09023-3	23	29	3	
*	09023-3.5	23	30	3.5	
*	09023-3.6	23	30.2	3.6	
*	09023-4	23	31	4	
*	09023-4.5	23	32	4.5	
*	09023-5	23	33	5	
*	09023-6	23	35	6	
	08317	23.16	33.82	5.33	AS-317
	071023	23.3	27.1	1.9	JASO-1023
	072023	23.3	28.1	2.4	JASO-2023
*	02024	23.4	29.6	3.1	G-24
	08213	23.4	30.46	3.53	AS-213
	08119	23.47	28.71	2.62	AS-119
	08912	23.47	29.37	2.95	AS-912
*	09023.5-1.5	23.5	26.5	1.5	
*	09023.5-1.7	23.5	26.9	1.7	
	04024	23.5	27.5	2	S-24
*	09023.5-3	23.5	29.5	3	
	09023.5-4	23.5	31.5	4	V-24
	08021	23.52	27.08	1.78	AS-021
*	09023.6-5	23.6	33.6	5	
*	09023.65-8	23.65	39.65	8	
	01024	23.7	30.7	3.5	P-24
*	09023.9-0.8	23.9	25.5	0.8	
*	09024-1	24	26	1	
*	09024-1.3	24	26.6	1.3	
*	09024-1.5	24	27	1.5	

* 符號代表國際規範外， 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)