






氣動系列
Pneumatic

GLY 免給油
(Piston & Rod Seal)

材質 Material : NBR 76° Non-Lubricated, FKM



適用範圍 Service range	
溫度 Temperature	-20 ~ 80 °C
壓力 Pressure	10 kgf/cm ²
速度 Speed	0.5 m/s

單位 unit: mm

CNL 編號 Parts No.	金屬尺寸 Groove dimensions		迫緊尺寸 Packing dimensions 高度 H
	內徑 d	外徑 D	
GLY- 10	10	18	5
GLY- 12	12	20	5
GLY- 14	14	22	5
GLY- 16	16	24	5
GLY- 17	17	25	5
GLY- 18	18	26	5
GLY- 20	20	28	5
GLY- 22.4	22.4	30	5
GLY- 25	25	33	5
GLY- 27	27	35	5
GLY- 28	28	36	5
GLY- 30	30	40	6
GLY- 31.5	31.5	41.5	6
GLY- 32	32	42	6
GLY- 35	35	45	6
GLY- 35.5	35.5	45.5	6
GLY- 36	36	46	6
GLY- 40	40	50	6
GLY- 45	45	55	6
GLY- 50	50	60	6
GLY- 53	53	63	6
GLY- 55	55	65	6
GLY- 60	60	70	6
GLY- 63	63	73	6
GLY- 65	65	75	6

CNL 編號 Parts No.	金屬尺寸 Groove dimensions		迫緊尺寸 Packing dimensions 高度 H
	內徑 d	外徑 D	
GLY- 70	70	80	6
GLY- 75	75	85	6
GLY- 80	80	90	6
GLY- 85	85	100	9
GLY- 95	95	110	9
GLY- 100	100	115	9
GLY- 105	105	120	9
GLY- 110	110	125	9
GLY- 115	115	130	9
GLY- 125	125	140	9
GLY- 135	135	150	9
GLY- 145	145	160	9
GLY- 160	160	175	9
GLY- 165	165	180	9
GLY- 175	175	190	9
GLY- 180	180	200	12
GLY- 185	185	205	12
GLY- 200	200	220	12
GLY- 215	215	235	12
GLY- 230	230	250	12
GLY- 240	240	260	12

* 產品陸續推出中，請先來電洽詢
Size increasing, please call for checking.

